



Disty DECT Base Duo - 2 Line DECT

The disty base duo is a DECT/GAP base station for universal use with up to 8 GAP handsets or the disty box³⁰⁰ or disty box⁵⁰⁰⁰. It is the ideal solution for operating two analogue lines on a low-cost DECT system.

The distybase duo can be employed in a variety of ways in the home and office, both directly on the public phone network and as a small-scale DECT solution on PABXs.

The distybase duo exant version, connected to an external aerial, and can bridge distances of up to 9 km when used in combination with the disty box⁵⁰⁰⁰.

Technical data

- DECT (Digital Enhanced Cordless Telecommunications)
- GAP (Generic Acces Protokoll)
- CLIP
- Frequency range: 1880 MHz to 1900 MHz
- Transmission output: 10 mW on average
- Voice transmission at 32 kbit/s ADPCM
- Fax mode: group 3, V.29 at maximal 9600 bit/s
- Modem operation at max. 9600 bit/s
- 2 analog wire
- Dialling procedure: DTMF
- number of GAP mobilparts: 8
- Flash time: adjustable to 2550 ms
- Display unit: Leuchtdiode (LED) for exchange access/registration
- Operation unit: button for registration
- Dimensions: 120 x 100 x 38 mm (W x H x D)
- Weight: 130g
- Mounting location: wall mounting indoors
- Power supply: 6 V AC/8 V DC (+/-15 %), 180 mA zero signal current, maximum 300 mA
- Conforms to EN 60950:2000, TBR 21, ETS 300 444, ETS 300 659-1/300 778-1, EN 301 406; TBR 10
- CE certification
- Scope of delivery: distybase duo; AC adapter 230 V, 50 Hz; connection cable for telephone line; user guide

