



Disty DECT Duo Exant - 2 Line Long Range DECT

Works under the same principle and with the same uses in mind as the Disty Base Duo, but using an external aerial and in conjunction with the disty box⁵⁰⁰⁰ distances of up to 9km can be bridged.

Technical Data

- DECT (Digital Enhanced Cordless Telecommunications)
- GAP
- CLIP
- Frequency range: 1880 MHz to 1900 MHz
- Transmission output: 10 mW on average
- Voice transmission at 32 kbit/s ADPCM
- Fax mode: group 3, V.29 at maximal 9600 bit/s
- Modem operation at max. 9600 bit/s
- 2 analog wire
- Dialling procedure: DTMF
- Number of GAP mobilparts: 8
- Flash time: adjustable to 2550 ms
- Display unit: Leuchtdiode (LED) for exchange access/registration
- Operation unit: button for registration
- Dimensions: 120 x 100 x 38 mm (W x H x D)
- Weight: 130g
- Mounting location: wall mounting indoors
- Power supply: 6 V AC/8 V DC (+/-15 %), 180 mA zero signal current, maximum 300 mA
- Conforms to EN 60950:2000, TBR 21, ETS 300 444, ETS 300 659-1/300 778-1, EN 301 406; TBR 10
- Scope of delivery: distybase duo; AC adapter 230 V, 50 Hz; connection cable for telephone line; user guide